Model: WL-UG69PD13 Pro **Datasheet V1.0** **2023.9.4**

USB-C Triple 4K Display Universal Docking Station support Power Delivery

The 69PD13 docking station uses the most advanced USB-C and DisplayLink technology. 10Gbps bandwidth, up to 100W charging power supply, provides three 4K@60Hz video outputs via DisplayPort and HDMI ports. In addition, the port extends your laptop to three 5Gbps USB-A ports, two 10Gbps USB-C ports, which support BC1.2 fast charging, a 1Gbps wired Ethernet connection, an SD 3.0 card reader with Micro SD, and more. A very advanced 3.5mm headphone audio jack.





FEATURES

- Provide USB-C 3.1 Gen2 Laptops and MacBook's Computer with Triple 4K/60Hz video output via Universal Docking even monitors interface is HDMI or DisplayPort.

- 2 x Stream HDMI/DisplayPort 4K@60Hz, also support USB3.0/2.0 computer.

- Supports USB Power delivery up to 100W upstream Charging for laptop.

- SD V3.0 /Micro SD Card Reader slot data transfer speed up to 104MB/s.

website - www.konnexlinq.com

- 2 USB3.0 Type-C (10G) ports One of which supports BC1.2 fast charging expansion for connecting more USB devices.

- three USB3.0 Type- A (5G) ports to extend more connectivity to USB devices.

- Ethernet port supports up to 1 Gbps (10/100/1000Mbps).

- Integrated TRRS 4-pole phone jack to give audio speaker out and mic.

SPECIFICATION

Connection To Host		
Plug & Play	1) Requires 3 HDMI or 2 display ports 2) Plug & Play for rest functions	
USB Power Delivery	Supports USB PD 3.0 100Watt Power Delivery	Solution:FL7102+SC8886
USB Port	2 x USB-C 10Gbps ports to extend more connectivity to USB devices	Solution: GL3590
	3 x USB-A 5Gbps ports to extend more connectivity to USB devices	Solution: GL3523

Video Ports	3 x HDMI ports 2 x DisplayPort	Solution: DL6950&VMR7100
Audio	Integrated TRRS 4-pole phone jack	Solution: DL6950
Card Reader	Integrated SD V3.0 Card Reader	Solution: GL3224
Ethernet Speed	1x RJ45 10/100/1000Mbps Ethernet	Solution: YT8531DC
LED	1 x Power LED	
Button	ON/OFF button to turn the docking station on and off	
Power Adapter	1x DC20V/6.5A 130Watt（Brick Style）	
Operating Systems	Microsoft Windows 10/11 Apple Mac OS 11 or later	

MAX DISPLAY RESOLUTION

(1) Scenarios for HDMI/DP ports, the dock can be connected with USB-C or USB-A computers whether it’ s USB3.2/3.0/2.0 protocols

Scenarios	Systems	Resolution

Single Display	HDMI1/DP1	4K@60HZ
	HDMI2/DP2	4K@60HZ
	HDMI3	4K@60HZ
Dual Displays	HDMI1/DP1	4K@60HZ
	HDMI2/DP2	4K@60HZ
	HDMI3	4K@60HZ
Triple Displays	HDMI1/DP1	4K@60HZ
	HDMI2/DP2	4K@60HZ
	HDMI3	4K@60HZ
*Note:HDMI3(Alt Mode)prot supports 4K@30Hz DP1.2 and supports 4K@60Hz in DP1.4		

PHYSICAL

Product Dimensions	66 x 122.2 x 185 mm (WxDxH)
Product Weight (g)	

Material	ABS plastic
Working Environment	Operation temperature: Storage temperature: Operation RH (relative humidity): Storage RH:
Compliance	FCC, CE, ROHS, etc
In the box	1 x USB-C to C Cable 1 x DC20V 6.5A Power adapter 1 x AC power cable 1 x lock wire shell 1 x Quick start guide